

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Konica Minolta | Logo |
|---|---|------|
| Company name * | Konica Minolta Europe GmbH | |
| Contact information * e-mail address | https://wwws.konicaminolta.net/neoga/gl/about.php | |
| Internet site * | http://www.konicaminolta.com/index.html | |
| Additional information | | |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. | | | | | |
|--|--|--|--|--|--|
| Type of product * | Multifunction Printer | | | | |
| Commercial name * | bizhub | | | | |
| | | | | | |
| Model number * | 4052 | | | | |
| Issue date * | 1 June 2018 | | | | |
| Intended market * | 🗌 Global 🛛 Europe 🗌 Asia, Pacific & Japan 🔲 Americas 🗌 Other | | | | |
| Additional information | version 1.0 | | | | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

| Model number * | | bizhub 4052 | Logo | | | |
|----------------|--|---|--------------|--------------|----|------|
| Issue da | te * | 1 June 2018 | | | | |
| | | | | | | |
| | | | | | | met |
| Item | Herende | | | Yes | No | n.a. |
| P1.1* | | bus substances and preparations to do comply with the current European RoHS Directive. (See legal reference and N | | | | |
| | | | | \mathbf{X} | | |
| P1.2* | | e do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value. | | \boxtimes | | |
| P1.3* | | do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), | | \times | | |
| | trichloro | pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no n ration values. | | 1- | | |
| P1.4* | | do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych (PCT) in preparations (see legal reference). | lorinated | \boxtimes | | |
| P1.5* | | e do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car ntaining at least 48% per mass of chlorine in the SCCP (see legal reference). | bon atoms | in the | | |
| P1.6* | (see lega | h direct and prolonged skin contact do not release nickel in concentrations above (al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5. |),5 μg/cm²/\ | week 🔀 | | |
| P1.7* | REACH | Article 33 information about substances in articles is available at (add URL or mail nicaminolta.eu | contact): | \boxtimes | | |
| P2 | Batterie | | | | | |
| P2.1* | | buduct contains a battery or an accumulator, the battery/accumulator is labeled with Information on proper disposal is provided in user manual. (See legal reference) | the disposa | | | |
| P2.2* | Batteries referenc | or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadn e) | nium. (See | legal 🔀 | | |
| P2.3* | Batteries | and accumulators are readily removable. (See legal reference) | | \boxtimes | | |
| P3 | Conform | nity verification & Eco design (ErP) | | | | |
| P3.1* | | duct is CE-marked to show conformance with applicable legal requirements (see legal requirements) and laration of Conformity can be requested at (add link or e-mail address): <i>env@konic</i> | | | | |
| P3.2* | | luct complies with the Eco design requirements for energy-related products, al reference). | | \boxtimes | | |
| | Required information is; Zigiven in item P15 or added to this document, | | \boxtimes | | | |
| | | available at (add URL): | | | | |
| P4 | Consum | able materials | | | | |
| P4.1* | | o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and NOTE B1). | ax 0,01% (s | ee 🔀 | | |
| P4.2* | If ink/ton | er is used in the product, it does not contain cadmium max 0,1% by weight (see leg | gal referenc | e). 🗙 | | |
| P4.3* | .3* If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there are Community workplace exposure limits, the product/packaging is adequately labeled according to applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference). | | | | | |
| P5 | | packaging | | | | |
| P5.1* | Packagi | ng and packaging components do not contain more than 0,01% lead, mercur ant chromium by weight of these together. | y, cadmiun | n and 🔀 | | |
| P5.2* | The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s used (see legal reference). | | rial(s) 🔀 | | | |
| P5.3* | The proc | luct packaging material is free from ozone depleting substances as specified in the l al reference). | Montreal Pr | otocol 🔀 | | |
| | Comme | nt: Legal reference has no maximum concentration values. | | | | |
| P6 | | nt information | | | | |
| P6.1* | Informati | on for recyclers/treatment facilities is available (see legal reference). | | \boxtimes | | |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model nu | umber * | bizhub 4052 Lo | go | | | |
|-----------|--|--|-------------|--------------|--------------|----------|
| Issue dat | te * | 1 June 2018 | | | | |
| | | | | | | |
| | | mental attributes - Market requirements (See General NOTE GN below) | | | | |
| | | nental conscious design | | Require | | |
| Item | | tory to fill in. Additional information regarding each item may be found under P14. | | Yes | No | n.a. |
| P7 | Design | nbly, recycling | | | | |
| P7.1* | | t have to be treated separately are easily separable | | \square | | |
| P7.2* | | aterials in covers/housing have no surface coating. | | | + | |
| P7.3* | | arts > 100 g consist of one material or of easily separable materials. | | | <u> </u> | <u> </u> |
| P7.4* | | | | \square | <u> </u> | <u> </u> |
| | | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | | \square | <u> </u> | <u> </u> |
| P7.5 | | arts are free from metal inlays or have inlays that can be removed with commonly availa | ble tools. | \mathbf{X} | | |
| P7.6* | | e easily separable. (This requirement does not apply to safety/regulatory labels). | | \mathbf{X} | | |
| | Product | | | | | |
| P7.7* | | g can be done e.g. with processor, memory, cards or drives | | \mathbf{X} | | |
| P7.8* | | g can be done using commonly available tools | | \mathbf{X} | | |
| P7.9. | | rts are available after end of production for: 5 years | | | | |
| P7.10 | Service is | s available after end of production for: 5 years | | | | |
| | | and substance requirements | | | | |
| P7.11* | | cover/housing material type (e.g. plastics, metal, aluminum): | | | | |
| P7.12 | | ype: ABS Material type: PC+ABS Material type materials of external electrical cables are PVC free. | 9: | | | |
| | | | | | \mathbf{X} | |
| P7.13 | | n materials of internal electrical cables are PVC free. | | | \boxtimes | |
| P7.14 | weight (1 polyvinyl | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromir 000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame reta chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in part n 25% post-consumer recycled content. | irdants, an | id 💆 | | |
| P7.15 | Printed ci | rcuit boards, PCBs (without components) are low halogen: all 🗌 PCBs > 25 g 🔲 are | low haloge | en 🗌 | \boxtimes | |
| | | d in IEC 61249-2-21. (See NOTE B2) | | | | |
| P7.16 | Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Image: FR(40) Marking: FR(40) | | | | | |
| P7.17 | <u>Alt. 1:</u> Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): | | | | | |
| | TBBPA (additive) \Box , TBBPA (reactive) \Box (See NOTE B3), Other; chemical name: , CAS #: | | | | | |
| | <u>Alt. 2:</u> Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: <i>FR(16)</i> | | | | | |
| P7.18 | concentra 1. Chemi 2. Chemi | ame retarded plastic parts > 25 g contain the following flame retardant substances/pre ations above 0,1%: cal name: , CAS #: (See NOTE B4) cal name: , CAS #: " cal name: , CAS #: " | parations i | in | | |
| | | emical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: $FR(17), FR(40), FR(30+40)$ | | \boxtimes | | |
| P7.19 | In plastic assigned | parts > 25 g, flame retardant substances/preparations above 0,1% are used which have the following Risk phrases; and Hazard statements: | e been | | | |
| P7.20* | | ce(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) umer recycled plastic material content is used in the product (See NOTE B6): | | | | |
| | lf YES; at a) Of to perc | t least one of the two alternatives below shall be answered; btal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (cal centage of total plastic by weight) is 40 %. | culated as | a | | |
| | or b) The | weight of recycled material is g. | | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model nu | mber * | bizhub 40 | 052 | | | Logo | | | |
|---|-----------------------------------|--------------------------------|---|----------------------------|---|-------------------------------|--------------|-------------|-------------|
| Issue dat | e * | 1 June 20 | 018 | | | | | | |
| Product | environr | nental att | ributes - Market re | equirements (cor | ntinued) | | Requi | rement | met |
| Item | | | | | | | Yes | s No | n.a. |
| D7 04* | | | ance requirements | | | | | | |
| P7.21* Biobased plastic material content is used in the produc | | | | | | | | \boxtimes | |
| | a) Of tota | total plastic al plastic by | of the two alternative parts' weight > 25 g weight) is %. | , the biobased plast | swered; ic material content (calcu | ulated as a perce | ntage of | | |
| P7.22* | Light sou | urces are fre | ee from mercury, i.e. pecify: Number of lan | less than 0,1 mg/lar | np. um mercury content per l | amp: mg | \mathbf{X} | | |
| P8 | Batterie | s | | | | | | | |
| P8.1* | Battery of | hemical co | mposition: Lithiur | m Manganese diox | ide | | | | |
| P9 | Energy | consumpti | on (See NOTE B8) | | | | | | |
| P9.1 | For the p | product the | following power level | s or energy consum | ptions are reported: | | | | |
| Energy m | ode * | | Power level at 100 V AC | Power level at 115 V AC | Power level at 230 V AC | Reference/Sta modes and te | | energy | |
| | de for ENE perational lucts | | W | W | W | | | | \boxtimes |
| Standby/off mode for ENERGY STAR Operational Mode (OM) products | | erational | W | W | W | | | | \boxtimes |
| TEC value for ENERGY STAR TEC products | | GY STAR | 1.4 kWh/week | 1.5 kWh/week | 1.4 kWh/week | Energy Star | | | |
| (TEC= Ty Maximun | pical Enero | ЗУ | W | W | W | | | | |
| | | | | | | Compared a | a se da se d | | |
| Active (P | rinting) | | 536 W | 546 W | 532 W | Corporate St | andard | | |
| Ready | | | 22.3 W | 23.6 W | 24.0 W | Energy Star | | | |
| Sleep | | | 1.27 W | 1.51 W | 1.30 W | Energy Star | | | |
| Hibernate | 9 | | W | W | 0.40 W | IEC 62301 | | | |
| Plug-in o | ff | | 0.003 W | 0.001 W | 0.007 W | IEC 62301 | | | |
| External F | Power Supp | oly Efficienc | ncy Level (International Efficiency Marking Protocol) * : | | | | | \times | |
| Print/Scar | n Speed * | : | 0 images per minute | | | | | | |
| Default tin | ne to enter | energy sav | ve mode: 1 minute | S | | | | | |
| P9.2* | | | e energy save function | | he product. | | X | | |
| P10 | Emissio | | 0, 11 110 | | • | | | | |
| | | | Declared according to | ISO 9296 (See NO | TE B9) | | | | |
| P10.1 | Mode | | ode description | | Statistical upper limit A- $L_{WA,c}$ (B) | weighted sound p | oower level, | | |
| | Idle | * | Ready | | * 3.1 | | | | |
| | Operatio | | * Printing (Duplex b/w) | | * 7.0 | | | | |
| | Other m | | Printing (Simple b/w | | 7.0 | | | | |
| | Measure | ed according | g to: 🛛 ISO 7779 🛛 🗌 Other (only | ECMA-74 | CMA-74) | | | | |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

| Issue date ' | * | 1 June 2018 | | | | |
|--|---|---|--|---|---------------------------|------|
| Issue date * | | | | | | |
| Product environmental attributes - Market requirements (continued) | | | | Requir | ement | met |
| Item | | | | Yes | No | n.a. |
| | | al emissions from printing products (See NOTE B10) | | | | |
| | | formed according to ECMA-328 Determination of Chemical Emission Rates from E | lectronic | \boxtimes | | |
| | | ent (ISO/IEC 28360) , other specify: RAL UZ-205 emission rate (operation phase) is (mg/h): | | | | |
| | Electrop | hotographic devices: Ozone <0.28 (LOQ) Dust 0.83 Styrene 0.13 Benzene < TVOC 6.9 | <0.01 (LO | २) | | |
| | Ink devi | | ; | | | |
| | Note: co | mpliance with maximum emission rates in eco labels to be declared in P14. | | | | |
| | | nable materials for printing products | | | | |
| | | / Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ | | · 🔼 | | |
| | EN 1228 | | ne require | ments of | | |
| P11.3* | 2-sided | (duplex) printing/copying is an integrated product function. | | \boxtimes | | |
| P11.4* | The pro | duct is delivered to end-user with default auto-duplex enabled. | | \boxtimes | | |
| | | ing and documentation | | | | |
| | Product Product Product Product Product Product Product | packaging material type(s):Corrugated packaging material type(s):weight (kg):3.81 weight (kg):packaging material type(s):Plastic- HDPE packaging material type(s):weight (kg):0.15packaging material type(s):Cother weight (kg):weight (kg):0.26packaging material type(s):weight (kg):weight (kg):packaging material type(s):weight (kg):weight (kg): | | | | |
| | | plastic primary packaging is free from PVC. | | \boxtimes | | |
| | | duct primary corrugated fiberboard packaging, specify the contained percentage er recovered fiber content: Recycled content >25 % | of minim | um post- | | |
| | | media for user and product documentation (tick box): nic 🛛 , Paper 🖾 , Other 🔲 | | | | |
| P13.5 | (Please User an | only complete this item if paper documentation used) d product documentation on paper media is chlorine-free: please specify: | | \boxtimes | | |
| | Totally o | chlorine-free | | \boxtimes | | |
| | Element | tal chlorine-free | | | | |
| | Process | ed chlorine-free | | | | |
| P14 | Volunta | iry programs: | | | | |
| P14.1 | The pro | duct meets the requirements of the following voluntary program(s): | | | | |
| | - | el: Blue Angel Criteria version: RAL- UZ 205 Date: Jan. 2017 Product d | | Imaging Equipn Office Equipme | | |
| | Eco-lab | el: Criteria version: Date: Product of | category: | | | |
| | | nal information (See NOTE B11) | | | | |
| | labeled P2.3 - 1 the cus P3.2 - 1 P5.2 - 1 when th P7.14 - bromin P7.20 - | The battery contained within this product should be disposed of properly with with the WEEE disposal symbol and instructions for such disposal is listed in "he battery contained within this product meets the exception listed. The batter tomer; however, is designed for easy removal by recyclers and service provid This product complies with Lot 6 and Lot 26 of Eco design Requirement. The packaging materials are marked with abbreviations and numbers indicatin rey are >25g A small amount of bromine may be present in covers due to sourcing post-co e was intentionally added in the processing of these parts. Per IEEE 1680.2 PCR calculation | n the proc ery is not ders. Ig the nati | luct User's Gui intended to be ure of the mater | de remove rial(s) u | d by |
| BTU . (230v) | 28.4 BT | U/h The figure is based on the TEC value of 1.4 kWh/week (=24h x 7days) | | | | |
| | 30.5 BT | U/h The figure is based on the TEC value of 1.5 kWh/week (=24h x 7days) | | | | |

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

| Reference | Declaration item |
|---|------------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1, P4.1 |
| (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances) | P1.3, 5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| "REACH" Regulation (1907/2006), annex VII | P1.10 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II) | P4.3 |
| Regulation (EC) 1272/2008 (CLP Regulation) | P4.3, P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |